

# Model 43-93 Alpha-Beta Scintillation Detector

Part Number: 47-2556



# **Specifications**

INDICATED USE: simultaneous alpha and beta survey SUGGESTED INSTRUMENTS: Model 2360, Model 3002, Model 3003

**DETECTOR TYPE**: ZnS(Ag) adhered to 0.25 mm (0.01 in.) thick

plastic scintillator

**WINDOW**: 1.2 mg/cm<sup>2</sup> metalized polyester

**WINDOW AREA:** 

Active: 100 cm<sup>2</sup> (15.5 in<sup>2</sup>) Open: 88 cm<sup>2</sup> (13.6 in<sup>2</sup>)

PROTECTIVE SCREEN: 0.79 mm (0.031 in.) thick, 6.5 mm

(0.26 in.) square openings, 88% open

Outer Dimensions (L x W): 168 x 92 mm (6.6 x 3.6 in.) Tool-less removal for quick window replacements **EFFICIENCY (4π**): <sup>99</sup>Tc: 15%, <sup>90</sup>Sr/<sup>90</sup>Y: 20%, <sup>239</sup>Pu: 20%

TYPICAL BACKGROUND:

Alpha: 3 cpm or less Beta: 300 cpm or less

### CROSSTALK:

Alpha to Beta: 10% or less Beta to Alpha: 1% or less

**DETECTOR UNIFORMITY:** within 15% of average reading **GAMMA SENSITIVITY:** 15 to 20 cpm per  $\mu$ R/hr ( $^{137}$ Cs) **PHOTOMULTIPLIER TUBE:** 29 mm (1.125 in.) diameter **OPERATING VOLTAGE:** typically 500 to 1200 V (1500 V max.)

**TEMPERATURE RANGE**: -20 to 40 °C (-4 to 104 °F)

**ENVIRONMENTAL RATING:** IP rating of 63

**CONNECTOR**: series "C", unless otherwise specified **CONSTRUCTION**: aluminum with beige powder coating **SIZE (H x W x L)**: 6.4 x 9.5 x 31 cm (2.5 x 3.8 x 12.3 in.)

**WEIGHT**: 0.45 kg (1.0 lb)

## Also Available

**High Temperature Version:** This version has a plastic scintillator designed for use at higher temperatures, up to 50 °C (122 °F). [PN: 47-4468]

# **Optional Protective Screens**

- PN 7393-208: 0.79 mm (0.031 in.) thick, 4.8 mm (0.19 in.) hex openings, 83.5% open
- PN 7393-209: 0.79 mm (0.031 in.) thick, 4.0 mm (0.16 in.) square openings, 81% open
- PN 7393-138: 0.51 mm (0.020 in.) thick, 6.5 mm (0.26 in.) square openings, 88% open
- PN 2393-345: 0.79 mm (0.031 in.) thick, fine stainless steel mesh openings, 88% open