

Model 4906P Alpha/Beta/Gamma Hand & Foot Monitor

Part Number: 48-3919

Features

- GM Pancake Detectors
- Large LCD User Interface
- Automatic Routines for Detector Setup & Alarm Calculations
- Customizable Voice Prompts
- Single-Hand Operational Mode
- Front Access to All Components for Repair/Calibration

Introduction

The Model 4906P is a low cost, industrial duty, alpha/beta/gamma contamination monitoring system that uses six clusters of pancake detectors for checking personnel. A large color LCD presents users with the system status and points out any potential contamination in an easy-to-use manner. Alarms are annunciated locally and can be augmented with optional relays for signaling remote devices or a light stack mounted on top.

All maintenance can be performed from the front of the instrument. Detector access for quick replacement or repair is facilitated by hinged top covers. The unit is equipped with rear-mounted wheels to facilitate transporting the instrument from one location to the next.



(shown with optional Status Light Tower)

Specifications

DETECTORS: six clusters of pancake detectors: two 6-pancake clusters for feet, and four 5-pancake clusters to cover both sides of hands

EFFICIENCY (4 π):

Hand: ^{14}C - 3%; ^{99}Tc - 12%; ^{137}Cs - 12%; ^{239}Pu - 12%; $^{90}\text{Sr}/^{90}\text{Y}$ - 23%; ^{57}Co - 0.15%

Foot: ^{14}C - 3%; ^{99}Tc - 10%; ^{137}Cs - 10%; ^{239}Pu - 12%; $^{90}\text{Sr}/^{90}\text{Y}$ - 23%; ^{57}Co - 0.15%

DISPLAY: 30.7 cm (12.1 in.) diagonal, TFT LCD SVGA

ELECTRONICS: fanless motherboard running Windows™ 7 Pro

COUNT TIME: adjustable from 1–99 seconds

CONTROLS: LCD touchscreen facilitates all control functions with the exception of 1) power on/off button, 2) one hand operation button, 3) alarm acknowledgment button

CONSTRUCTION: welded aluminum with powder coat finish, stainless steel base, and two offset wheels for portability

TEMPERATURE: 0 to 40 °C (32 to 104 °F)

HUMIDITY: 0–95% RH

POWER:

Input: 90 – 264 VAC at 47 – 63 Hz (requirement for wall outlet power)

Output: 12 Vdc, 7 A Max, 84 W (Model 4906 input power coming from Power Supply)

SIZE: 121 x 79.8 x 90.2 cm (47.6 x 31.4 x 35.5 in.) (H x W x D), step-up 3.8 cm (1.5 in.) high


WEIGHT: 72.6 kg (160 lb)

Options:

- **Light Tower** with Red, Yellow, and Green Status Signal Lights (PN 4420-335)
- **Pancake Frisker:** Model 44-9 with cable, infrared sensor, holder, & components for determining point of contamination in the event of an alarm (PN 4420-420)

Also Available:

- **Model 4906A** Alpha Hand & Foot Monitor (PN 48-3687)
- **Model 4906AB** Alpha/Beta Hand & Foot Monitor (PN 48-3688)



Frisker Option PN 4420-420